





## DPCW35



### Specification

Electricity	DPCW35-J	220V, 60Hz, 1PH	Power Consumption	DPCW35-J	2800 W			
	DPCW35-A	208~240V, 50/60Hz, 1PH		DPCW35-A				
	DPCW35-E	220~240V, 50/60Hz, 1PH		DPCW35-E				
	DPCW35-CE1	220~240V, 60Hz, 1PH		DPCW35-CE1				
	DPCW35-J	200V, 50/60Hz, 1PH		DPCW35-J				
Power Connection		Plug type	Max Current		12 A			
Conversion to Calory		2419.2 Kcal/h						
Warming		H1 ~ H7 (7 steps)	Heating		1 ~ 10 (10 steps)			
Output per Warming Steps		H1	H2	H3	H4	H5	H6	H7
		40Wh	60Wh	100Wh	130Wh	170Wh	240Wh	350Wh
Dimension / Weight		375 X 450 X 223 (mm) / 12kg						
Controller Type		Capactive button (integrated into the unit)						
Burner Diameter		Ø300mm	Burner Glass R Value		R205			
Preferred Wok Pan Diameter		Ø360mm	Burner Depth		65 mm			
Functions & Features		<input checked="" type="checkbox"/> Safety						
		- No vessel : "00"						
		- Over current indication : "E1"						
		- Over voltage indication : "E2" ( Above 265V )						
		- Low voltage : "E3" ( Below 180V )						
		- Over heated product indication : "E4" ( Heatsink temperature above 85°C )						
		- Top surface(top glass) overheated : "E6" ( Top surface temperature above 230°C )						
- Unstable power indication: "E7"								
- Defective PCB indication : "E8"								
- Defective Working Coil indication : "E9"								
Warranty		1 year (to be charged in case of user's negligence)						

Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

DIPO INDUCTION CO., Ltd. / www.dipoele.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.