

Drop-in Cooker (with Metal Casing)

NBK26



Specification

Electricity	NBK26	220V, 60Hz, 1PH	Power Consumption	NBK26	2600 W		
	NBK26-A	208~240V, 50/60Hz, 1PH		NBK26-A			
	NBK26-E	220~240V, 50/60Hz, 1PH		NBK26-E			
	NBK26-CE1	220~240V, 60Hz, 1PH		NBK26-CE1			
	NBK26-J	200V, 50/60Hz, 1PH		NBK26-J		2400 W	
Power Connection	Plug type		Max Current	12 A			
Conversion to Calory	2246.4 Kcal/h						
Warming	H1 ~ H7 (7 steps)		Heating	1 ~ 10 (10 steps)			
Output per Warming Steps	H1	H2	H3	H4	H5	H6	H7
	40Wh	60Wh	100Wh	130Wh	170Wh	240Wh	350Wh
Dimension / Weight	Product: 296 X 370 X 80 (mm) / 6.5kg Package: 490 X 360 X 180 (mm) / 7.1kg						
Controller Type	Jog dial, Capacitive button (separated from the unit)						
Power Cable	660 mm		Controller Cable	660 mm			
Cookware Diameter	min : Ø130mm max : Ø240mm		Loadable Weight	30 Kg			
Recommendation	Hotpot, Shabu shabu, Built-in on dining table						
Functions & Features	<input checked="" type="checkbox"/> Metal body makes the unit more durable						
	<input checked="" type="checkbox"/> Safety						
	- No vessel : "00"						
	- Over current indication : "E1"						
	- Over voltage indication : "E2" (Above 265V)						
	- Low voltage : "E3" (Below 180V)						
	- Over heated product indication : "E4" (IGBT heat sink temperature above 85°C)						
	- Top glass overheated (empty vessel) : "E5" (Top surface temperature above 200°C)						
	- Unstable power indication: "E7"						
	- Defective PCB indication : "E8"						
- Defective Working Coil indication : "E9"							
<input checked="" type="checkbox"/> Timer Setting							
- Between 0sec - 720min (12hr)							
Warranty	1 year (to be charged in case of user's negligence)						

Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

DIPO INDUCTION CO., Ltd. / www.dipoele.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.

Dimension (mm)	
Product	Installation Guide
Case Cut (using installation guide)	Case Cut (not using installation guide)
Table Cut (using installation guide)	Table Cut (for "L" type hole)
Control	Control Cut
<p>Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412</p> <p>R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412</p> <p>DIPO INDUCTION CO., Ltd. / www.dipoele.com</p> <p>COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.</p>	

Drop-in Cooker (with Metal Casing)

NBK35



Specification								
Electricity	NBK35	220V, 60Hz, 1PH			Power Consumption	NBK35	3500 W	
	NBK35-A	208~240V, 50/60Hz, 1PH				NBK35-A	3300 W	
	NBK35-E	220~240V, 50/60Hz, 1PH				NBK35-E	3500 W	
	NBK35-CE1	220~240V, 60Hz, 1PH				NBK35-CE1	3000 W	
	NBK30-J	200V, 50/60Hz, 1PH				NBK30-J	3000 W	
Power Connection		Plug type			Max Current		15 A	
Conversion to Calory		3024 Kcal/h						
Warming		H1 ~ H7 (7 steps)			Heating		1 ~ 10 (10 steps)	
Output per Warming Steps		H1	H2	H3	H4	H5	H6	H7
		40Wh	60Wh	100Wh	130Wh	170Wh	240Wh	350Wh
Dimension / Weight		Product: 296 X 370 X 80 (mm) / 6.5kg Package: 490 X 360 X 180 (mm) / 7.1kg						
Controller Type		Jog dial, Capacitive button (separated from the unit)						
Power Cable		660 mm			Controller Cable		660 mm	
Cookware Diameter		min : Ø125mm max : Ø240mm			Loadable Weight		30 Kg	
Recommendation		Hotpot, Shabu shabu, Built-in on dining table						
Functions & Features		<input checked="" type="checkbox"/> Metal body makes the unit more durable						
		<input checked="" type="checkbox"/> Safety						
		- No vessel : "00"						
		- Over current indication : "E1"						
		- Over voltage indication : "E2" (Above 265V)						
		- Low voltage : "E3" (Below 180V)						
		- Over heated product indication : "E4" (IGBT heat sink temperature above 85°C)						
- Top glass overheated (empty vessel) : "E6" (Top surface temperature above 260°C)								
- Unstable power indication: "E7"								
- Defective PCB indication : "E8"								
- Defective Working Coil indication : "E9"								
Warranty		<input checked="" type="checkbox"/> Timer Setting						
		- Between 0sec - 720min (12hr)						
Warranty		1 year (to be charged in case of user's negligence)						

Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

DIPO INDUCTION CO., Ltd. / www.dipoele.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.

Dimension (mm)	
Product	Installation Guide
Case Cut (using installation guide)	Case Cut (not using installation guide)
Table Cut (using installation guide)	Table Cut (for "L" type hole)
Control	Control Cut
<p>Control Wire Length = 660mm</p>	
<p>Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412</p> <p>R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412</p> <p>DIPO INDUCTION CO., Ltd. / www.dipoele.com</p> <p>COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.</p>	